



# DURADROP



## FUNCTIONALITY

<b>RF Protocol:</b>	EPC Class 1 Gen 2; ISO 18000-6C
<b>Operating Frequency:</b>	UHF - 860 to 960 MHz
<b>Memory Configuration:</b>	96 EPC Bits; 512 Bit User Memory
<b>R/W Capability:</b>	Read/Write

## PERFORMANCE

<b>Read Range:</b>	Up to 3ft (results may vary)
<b>Quality Guarantee:</b>	100%
<b>Orientation:</b>	Front Face Read
<b>IP Rating:</b>	IP68

## PHYSICAL

<b>Material:</b>	Stainless Steel
<b>Mounting System:</b>	Hook, Tie, Rope
<b>Color:</b>	Custom Logo Available (laser etching on back of product only)

## OPERATIONAL

<b>Continuous Max Service Temperature:</b>	257°F/ 125°C
<b>Continuous Min Service Temperature:</b>	-40°F/ -40°C
<b>Water and Ice Proof:</b>	Yes

## PRODUCT

<b>Weight:</b>	17g/ 0.59oz
<b>Dimensions:</b>	28.0 mm x 35.0 mm
<b>Thickness:</b>	4.65 mm



## RECOMMENDED TAG APPLICATIONS

**Oil & Gas:** Valves, Pipes & Industrial Equipment  
Tools & Machinery

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

(877) 747-2447

**What is it?**

[sales@infochip.com](mailto:sales@infochip.com)

**Is it safe to use?**

[www.infochip.com](http://www.infochip.com)