



DURAPLUG8



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 0.1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	PPA + GF30%
Mounting System:	Embeddable * No Adhesive Required*
Color:	Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

PRODUCT

Weight:	.27g/ .01 oz
Dimensions:	Diameter 0.315" (8mm)
Thickness:	.128" (3.25mm)



RECOMMENDED TAG APPLICATIONS

- Oil & Gas:** Downhole Drilling Tools
- Lifting:** Shackles, Hoist Rings, Hooks

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com