



# DURAZIP



### FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

### PERFORMANCE

Read Range:	Less than 1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

### PHYSICAL SPECIFICATIONS

Material:	PC/PBT
Mounting System:	Stainless Steel Cable
Color:	Custom Logo and Colors Available

### OPERATIONAL SPECIFICATIONS

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
IK Impact Rating:	IK10
Water and Ice Proof:	Yes

### PRODUCT DIMENSIONS

Weight:	40g/ 1.4 oz
Dimensions:	1.4" x 1.2"
Thickness:	0.7"
Cable:	Diameter 3.0 mm Length 12"



**RECOMMENDED TAG APPLICATIONS**  
Oil & Gas: Valves, Pipes & Industrial Equipment

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

(877) 747-2447

**What is it?**

[sales@infochip.com](mailto:sales@infochip.com)

**Is it safe to use?**

[www.infochip.com](http://www.infochip.com)