



MINIHANGTAG



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2: ISO 18000-6C
Operating Frequency:	UHF - 860 to 960 MHz
Memory Configuration:	96 Bit Serialized TID; 128-EPC Bit Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	1 to 50 ft (results may vary)
Quality Guarantee:	100%
Orientation:	Readable in 360° - Range varies with orientation
IP Rating:	IP68

PHYSICAL

Material:	Stainless Steel or Aluminum
Mounting System:	Adhesive, Attachment Holes, Hanging
Color:	Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	392°F/ 200°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	365°F/ 185°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	45g / 1.6 oz
Dimensions:	1.6" x 2"
Thickness:	.063"



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com