



SYNTHETIC TAG



FUNCTIONALITY

| | |
|-----------------------|--|
| RF Protocol: | ISO 15693 |
| Operating Frequency: | UHF |
| Memory Configuration: | 16 Character UID, 896 bits User Memory |
| R/W Capability: | Read/Write |

PERFORMANCE

| | |
|--------------------|---------------|
| Read Range: | Less Than 1" |
| Quality Guarantee: | 100% |
| Orientation: | Two Face Read |
| IP Rating: | IP68 |

PHYSICAL

| | |
|------------------|-------------------|
| Material: | Plastic |
| Mounting System: | String/Thread |
| Color: | Cream (Off White) |

OPERATIONAL

| | |
|-------------------------------------|--------------|
| Max Temperature Exposure: | 320°F/ 160°C |
| Min Temperature Exposure: | -40°F/ -40°C |
| Continuous Max Service Temperature: | 320°F/ 160°C |
| Continuous Min Service Temperature: | -40°F/ -40°C |
| Water and Ice Proof: | Yes |

DIMENSIONS

| | |
|-------------|--------------|
| Weight: | 1g / .04 oz |
| Dimensions: | Diameter .6" |
| Thickness: | .11" |



RECOMMENDED TAG APPLICATIONS

Lifting: Synthetic Slings & Harnesses

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com