



DURADROP



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2; ISO 18000-6C
Operating Frequency:	UHF - 860 to 960 MHz
Memory Configuration:	96 EPC Bits; 512 Bit User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 3ft (results may vary)
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	Stainless Steel
Mounting System:	Hook, Tie, Rope
Color:	Custom Logo Available (laser etching on back of product only)

OPERATIONAL

Continuous Max Service Temperature:	257°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

PRODUCT

Weight:	17g/ 0.59oz
Dimensions:	28.0 mm x 35.0 mm
Thickness:	4.65 mm



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Valves, Pipes & Industrial Equipment
Tools & Machinery

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>