

DURAPLUG9.5

100%

IP68

Front Face Read



RF Protocol: EPC Class 1 Gen 2; ISO 18000-6C Operating Frequency: UHF - (NA): 902 to 928 MHz (EU): 866 to 868 MHz Memory Configuration: 24 Character UID, 896 bits User Memory R/W Capability: Read/Write PERFORMANCE Read Range: Up to 18" (results may vary)

PHYSICAL	
Material:	PEEK + GF30%
Mounting System:	Injection Tool Required

OPERATIONAL

Max Temperature Exposure:	390°F/ 200°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	390°F/ 200°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes
Drilling Fluids:	Yes

PRODUCT

Weight:	.27g/ .01 oz
Dimensions:	Diameter .374" (9.5mm)
Thickness:	.169" (4.3mm)



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Downhole Drilling Tools, Pipe & Industrial Equipment, Subsea

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

Quality Guarantee:

Orientation:

IP Rating:

Holland RFID

(816) 421-2553

https://hollandnameplate.com/holland-rfid/