



DURATAB



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Less than 1"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	PC/PBT Alloy with Stainless Steel Frame
Mounting System:	Attachment Holes, Hanging
Color:	Custom Logo and Colors Available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
IK Impact Rating:	IK10
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	17.7g / .62 oz
Dimensions:	2" x 1"
Thickness:	.25"



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>