



DURATRAK



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2: ISO 18000-6C
Operating Frequency:	UHF - (NA): 865 to 956 MHz (EU): 865 to 956 MHz
Memory Configuration:	96 Bit Serialized TID; 128-EPC Bit Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 26.2 feet
Quality Guarantee:	100% & 2 years
Orientation:	Linear
IP Rating:	IP68

PHYSICAL

Material:	PC/ABS high impact
Mounting System:	Screw
Color:	Pantone blue 287C or grey

OPERATIONAL

Max Temperature Exposure:	185°F/ 85°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	185°F/ 85°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	0.5 oz/ 16 g
Dimensions:	3.6" x 1.1"
Width	0.6



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>