



DURAZIP SR



FUNCTIONALITY

| | |
|------------------------------|--|
| RF Protocol: | EPC Class 1 Gen 2; ISO 18000-6C |
| Operating Frequency: | UHF - 860 to 960 MHz |
| Memory Configuration: | 96-Bit EPC; 32-Bit User Memory; 48-Bit TID |
| R/W Capability: | Read/Write |

PERFORMANCE

| | |
|---------------------------|--------------------------------|
| Read Range: | Proximity (varies with reader) |
| Quality Guarantee: | 100% |
| Orientation: | Front Face Read |
| IP Rating: | IP68 |

PHYSICAL

| | |
|-------------------------|--|
| Material: | PC/PBT |
| Mounting System: | 3mm Stainless Steel Cable with Integrated Cable Lock |
| Color: | Custom Logo and Colors available |

OPERATIONAL

| | |
|--|--------------|
| Max Temperature Exposure: | 260°F/ 125°C |
| Min Temperature Exposure: | -40°F/ -40°C |
| Continuous Max Service Temperature: | 260°F/ 125°C |
| Continuous Min Service Temperature: | -40°F/ -40°C |
| Water and Ice Proof: | Yes |
| IK Impact Rating: | IK10 |

DIMENSIONS

| | |
|--------------------|----------------------------------|
| Weight: | 40g/ 1.4 oz |
| Dimensions: | 1.4" x 1.2" |
| Thickness: | 0.7" |
| Cable: | Diameter and Length Customizable |



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Valves, Pipes & Industrial Equipment

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>