



DURAZIP



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2; ISO 18000-6C
Operating Frequency:	UHF (EU) - 866 to 868 MHz (NA) - 902 to 928 MHz
Memory Configuration:	96-Bit EPC; 512 Bit User Memory; 64-Bit TID
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 5 feet (with handheld reader)
Quality Guarantee:	100%
Orientation:	Readable in 360° - Range varies with orientation
IP Rating:	IP68

PHYSICAL

Material:	PC/PBT
Mounting System:	3mm Stainless Steel Cable with Integrated Cable Lock
Color:	Custom Logo and Colors available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes
IK Impact Rating:	IK10

Product Dimensions

Weight:	40g/ 1.4 oz
Dimensions:	1.4" x 1.2"
Thickness:	0.7"
Cable:	Diameter and Length Customizable



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Valves, Pipes & Industrial Equipment

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>