

# MINIHANGTAG



#### **FUNCTIONALITY**

RF Protocol: EPC Class 1 Gen 2: ISO 18000-6C

Operating Frequency: UHF - 860 to 960 MHz

Memory Configuration: 96 Bit Serialized TID; 128-EPC Bit Memory

R/W Capability: Read/Write

#### **PERFORMANCE**

Read Range: 1 to 50 ft (results may vary)

Quality Guarantee: 100%

Orientation: Readable in 360° - Range varies with orientation

IP Rating: IP68

### **PHYSICAL**

Material: Stainless Steel or Aluminum

Mounting System: Adhesive, Attachment Holes, Hanging

Color: Custom Logo and Colors Available

#### **OPERATIONAL**

Max Temperature Exposure: 392°F/ 200°C

Min Temperature Exposure: -40°F/ -40°C

Continuous Max Service Temperature: 365°F/ 185°C

Continuous Min Service Temperature: -40°F/ -40°C

Water and Ice Proof: Yes

#### **DIMENSIONS**

Weight:	45g / 1.6 oz
Dimensions:	1.6" x 2"
Thickness:	.063"



#### RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more! For pricing and details, please call 1-816-421-2553.

## Holland RFID

(816) 421-2553

https://hollandnameplate.com/holland-rfid/