



NAMEPLATE TAG



FUNCTIONALITY

RF Protocol:	EPC Class 1 Gen 2: ISO 18000-6C
Operating Frequency:	UHF - 860 to 960 MHz
Memory Configuration:	96 Bit Serialized TID; 128-EPC Bit Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Up to 8"
Quality Guarantee:	100%
Orientation:	Front Face Read
IP Rating:	IP68

PHYSICAL

Material:	PC/PBT Alloy Tag/ Stainless Steel Nameplate
Mounting System:	Snap fit to custom nameplate tag
Color:	Custom Nameplate available

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	1.4g / .05 oz
Dimensions:	0.625" x .5"
Thickness:	.375"



RECOMMENDED TAG APPLICATIONS

Valve: Valves, Processing Plant equipment

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>