



BUTTON TAG HF



FUNCTIONALITY

RF Protocol:	ISO 15693
Operating Frequency:	HF - 13.56 MHz
Memory Configuration:	16 Character UID, 896 bits User Memory
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	Less Than 1"
Quality Guarantee:	100%
Orientation:	Two Face Read
IP Rating:	IP68

PHYSICAL

Material:	Plastic
Mounting System:	String/Thread
Color:	Cream (Off White)

OPERATIONAL

Max Temperature Exposure:	320°F/ 160°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	320°F/ 160°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	1g / .04 oz
Dimensions:	Diameter .6"
Thickness:	.11"



RECOMMENDED TAG APPLICATIONS

Lifting: Synthetic Slings & Harnesses

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID

(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>