



TACK TAG 2



FUNCTIONALITY

| | |
|------------------------------|---|
| RF Protocol: | EPC Class 1 Gen 2; ISO 18000-6C |
| Operating Frequency: | US: 902 to 238 MHz |
| Memory Configuration: | 96-Bit EPC; 512 User Bit Memory; 64-Bit TID |
| R/W Capability: | Read/Write |

PERFORMANCE

| | |
|---------------------------|--|
| Read Range: | Up to 7 feet (with handheld reader) |
| Quality Guarantee: | 100% |
| Orientation: | Readable in 360° - Range varies with orientation |
| IP Rating: | IP68 |

PHYSICAL

| | |
|-------------------------|-------------------|
| Material: | Stainless Steel |
| Mounting System: | Adhesive, Welding |

OPERATIONAL

| | |
|--|------------------------------------|
| Max Temperature Exposure: | 300°F/ 150°C |
| Min Temperature Exposure: | -40°F/ -40°C |
| Continuous Max Service Temperature: | 300°F/ 150°C |
| Continuous Min Service Temperature: | -40°F/ -40°C |
| Water and Ice Proof: | Yes (Not for continuous immersion) |

DIMENSIONS

| | |
|--------------------|----------------|
| Weight: | 8.5g / 0.28 oz |
| Dimensions: | 0.59" x 0.96" |
| Thickness: | 0.23" |



RECOMMENDED TAG APPLICATIONS

Oil & Gas: Industrial Equipment, Tools & Machinery

Visit www.hollandnameplate.com to learn about the Holland RFID suite of tags, readers and more!
For pricing and details, please call 1-816-421-2553.

Holland RFID
(816) 421-2553

<https://hollandnameplate.com/holland-rfid/>